



<b>Model</b>	GX 14 - 19 S
<b>Carrying Capacity</b>	14,000kg
<b>Cubic Capacity</b>	19m <sup>3</sup>
<b>Maximum Trailer Speed</b>	20mph
<b>Body</b>	Dimensions: 6100x2450x1370mm Hydraulically operated rear door Access ladder outside and inside body
<b>Floor Bearers</b>	80x40 steel box section
<b>Body Frame</b>	80x80 steel box section
<b>Top Rail</b>	80x80 steel box section
<b>Floor</b>	5mm steel
<b>Sides</b>	3mm steel
<b>Chassis</b>	250x150 box section
<b>Top Chassis</b>	150x100 box section
<b>Axles</b>	Granning 125mm ø 10 stud, 420x180 brakes
<b>Suspension</b>	Granning overslung 4 spring suspension Monoleaf springs
<b>Drawbar</b>	Sprung drawbar Heavy duty 40mm hitch eye Rear heavy 40mm tow eye welded to rear chassis
<b>Wheel Centres</b>	10 stud, fully welded high speed rims
<b>Tyres</b>	Remould 385/65Rx22.5 Tyres Mud wings and spray suppression flaps
<b>Braking</b>	Hydraulic braking system Ratchet style parking brake
<b>Lighting</b>	LED commercial road lighting system Connection to tractor: Removable electric coil Rear stop/tail/indicator lights with light guards Front marker lights Side marker lights High level rear marker lights Amber warning light
<b>Tipping Mechanism</b>	Twin 3 stage 3 3/4" chrome plated tipping rams 25mm ram pins with grease points 60mm hinge bar with bushes and grease points
<b>Paint</b>	Finished with 120 microns of two pack acrylic high gloss paint
<b>Optional Extras</b>	Fast tow trailer with air braking, ABS & LSV, Silage Sides, Roll over cover, Grain hatch, Flotation tyres, Front window/ view grille, High level road lights