



<b>Model</b>	GX 15 - LL
<b>Carrying Capacity</b>	15,000kg
<b>Maximum Trailer Speed</b>	20mph
<b>Body</b>	Standard width 2500mm (8'2") Beaver tail with spring assisted rear ramps
<b>Floor Bearers</b>	100x50 channel
<b>Floor</b>	50mm Keruing
<b>Side Rave</b>	150x75 channel with chain lashing bars and rope hooks
<b>Chassis</b>	250x150 box section
<b>Axles</b>	Granning 125mm ø 10 stud, 310x190 brakes
<b>Suspension</b>	Granning underslung 4 spring suspension
<b>Drawbar</b>	Heavy duty 40mm hitch eye
<b>Wheel Centres</b>	10 stud, fully welded high speed rims
<b>Tyres</b>	Double Coin 435/55Rx19.5
<b>Braking</b>	Spray suppression flaps Hydraulic braking system Ratchet style parking brake
<b>Lighting</b>	LED commercial road lighting system Connection to tractor: Removable electric coil Rear stop/tail/indicator lights Front marker lights Side marker lights Amber warning light
<b>Paint</b>	Finished with 120 microns of two pack acrylic high gloss paint
<b>Optional Extras</b>	Fast tow trailer fitted with air braking, ABS & LSV Lockable plastic or stainless steel toolbox Hydraulically operated rear ramps Rear wedge to carry boxes Removable Aluminium Ramps