



Model	GX 16 - 21 S
Carrying Capacity	16,000kg
Cubic Capacity	21m ³
Maximum Trailer Speed	20mph
Body	Dimensions: 6100x2450x1500mm Hydraulically operated rear door Access ladder outside and inside body Rope hooks on every body panel
Floor Bearers	80x40 steel box section
Body Frame	80x80 steel box section
Top Rail	80x80 steel box section
Floor	5mm steel
Sides	3mm steel
Chassis	250x150 box section
Top Chassis	150x100 box section
Axles	Granning 125mm ø 10 stud, 420x180 brakes
Suspension	Granning overslung 4 spring suspension 4 leaf springs
Drawbar	Sprung drawbar Heavy duty 40mm hitch eye Rear heavy duty hitch eye welded to rear chassis
Wheel Centres	10 stud, fully welded high speed rims
Tyres	Remould 385/65Rx22.5 Tyres Mud wings and spray suppression flaps
Braking	Hydraulic braking system Ratchet style parking brake
Lighting	LED commercial road lighting system Connection to tractor: Removable electric coil Rear stop/tail/indicator lights with light guards Front marker lights Side marker lights High level rear marker lights Amber warning light
Tipping Mechanism	Twin 3 stage 4.25" chrome plated tipping rams 35mm ram pins with grease points 60mm hinge bar with bushes and grease points
Paint	Finished with 120 microns of two pack acrylic high gloss paint
Optional Extras	Fast tow trailer with air braking, ABS & LSV, Silage Sides, Roll over cover, Grain hatch, Front window/view grille, High level road lights, Flotation tyres