



Model	GX 20 - 26 S
Carrying Capacity	20,000kg
Cubic Capacity	26m ³
Maximum Trailer Speed	Fast-tow trailer 80kph
Body	Dimensions: 7600x2500x1500mm Hydraulically operated rear door Full width front view grille with perspex cover Access ladder outside and inside body Rope hooks on every body panel Grain hatch
Floor Bearers	80x40 steel box section
Body Frame	80x80 steel box section
Top Rail	80x80 steel box section
Floor	5mm steel
Sides	3mm steel
Chassis	300x200 box section
Top Chassis	200x100 box section
Axles	Granning 125mm ø 10 stud, 420x180 brakes
Suspension	Granning overslung 4 spring suspension 4 leaf springs
Drawbar	Sprung drawbar Heavy duty 40mm hitch eye Rear heavy duty 40mm tow eyes welded to rear chassis
Wheel Centres	10 stud, fully welded high speed rims
Tyres	560/60Rx22.5 Tyres
Braking	Mud wings and spray suppression flaps Hydraulic. Air braking with ABS and LSV Connection to tractor: Dedicated ABS suzie Ratchet style parking brake
Lighting	Full LED commercial road lighting system Connection to tractor: Removable electric coil Rear stop/tail/indicator lights with rear light guards Front marker lights Three side marker lights each side High level rear marker lights on door frame Amber warning light
Tipping Mechanism	Single 170mm 5 stage tipping ram 60mm hinge bar with bushes and grease points
Paint	Finished with 120 microns of two pack acrylic high gloss paint
Optional Extras	Roll over cover Silage Sides High level road lights