



<b>Model</b>	GX 22 - LL
<b>Carrying Capacity</b>	22,000kg
<b>Maximum Trailer Speed</b>	20mph
<b>Body</b>	Standard Width 2500mm Beaver tail with spring assisted rear ramps
<b>Floor Bearers</b>	100x50 channel
<b>Floor</b>	50mm Keruing
<b>Chassis</b>	250x150 box section
<b>Axles</b>	Three Granning 125mm Ø 10 stud, 310x190 brakes
<b>Suspension</b>	Granning underslung sprung suspension Heavy duty 40mm hitch eye
<b>Wheel Centres</b>	10 stud, fully welded high speed rims
<b>Tyres</b>	Double Coin 435/50Rx19.5
<b>Braking</b>	Hydraulic braking system Ratchet style parking brake
<b>Lighting</b>	LED commercial road lighting system Connection to tractor: Removable electric coil Rear stop/tail/indicator lights with light guards Front marker lights Side marker lights Amber warning light
<b>Paint</b>	Finished with 120 microns of two pack acrylic high gloss paint
<b>Optional Extras</b>	Fast tow trailer with air braking, ABS & LSV, Lockable plastic or stainless steel toolbox, Hydraulically operated rear ramps, Rear wedge to carry boxes, Removable aluminium ramps