

## トラクター用ラジアルタイヤ



### EARTH-PRO

| サイズ       |         |        |           | チューブサイズ |        |
|-----------|---------|--------|-----------|---------|--------|
| サイズ       | 表記・速度   | 幅×外径   |           | チューブサイズ |        |
| 250/85R24 | 9.5R24  | 109 A8 | 246*1,037 | 9.5-24  | TR218A |
| 280/85R24 | 11.2R24 | 115 A8 | 282*1,086 | 11.2-24 | TR218A |
| 320/85R24 | 12.4R24 | 122 A8 | 336*1,148 | 12.4-24 | TR218A |
| 340/85R24 | 13.6R24 | 125 A8 | 356*1,181 | 13.6-24 | TR218A |
| 380/85R24 | 14.9R24 | 131 A8 | 391*1,245 | 14.9-24 | TR218A |
| 420/85R24 | 16.9R24 | 137 A8 | 418*1,315 | 16.9-24 | TR218A |
| 280/85R28 | 11.2R28 | 118 A8 | 280*1,190 | 11.2-28 | TR218A |
| 320/85R28 | 12.4R28 | 133 A8 | 325*1,246 | 12.4-28 | TR218A |
| 340/85R28 | 13.6R28 | 127 A8 | 343*1,289 | 13.6-28 | TR218A |
| 380/85R28 | 14.9R28 | 133 A8 | 380*1,357 | 14.9-28 | TR218A |
| 420/85R28 | 16.9R28 | 139 A8 | 418*1,420 | 16.9-28 | TR218A |
| 420/85R30 | 16.9R30 | 140 A8 | 438*1,468 | 16.9-30 | TR218A |
| 460/85R30 | 18.4R30 | 145 A8 | 478*1,524 | 18.4-30 | TR218A |
| 320/85R32 | 12.4R32 | 126 A8 | 325*1,357 | 12.4-32 | TR218A |
| 420/85R34 | 16.9R34 | 142 A8 | 418*1,578 | 16.9-34 | TR218A |
| 460/85R34 | 18.4R34 | 147 A8 | 479*1,637 | 18.4-34 | TR218A |
| 320/85R36 | 12.4R36 | 128 A8 | 325*1,458 | 12.4-36 | TR218A |
| 340/85R36 | 13.6R36 | 132 A8 | 345*1,495 | 13.6-36 | TR218A |
| 320/85R38 | 12.4R38 | 143 A8 | 325*1,509 | 12.4-38 | TR218A |
| 340/85R38 | 13.6R38 | 133 A8 | 345*1,543 | 13.6-38 | TR218A |
| 420/85R38 | 16.9R38 | 144 A8 | 418*1,679 | 16.9-38 | TR218A |
| 460/85R38 | 18.4R38 | 149 A8 | 455*1,747 | 18.4-38 | TR218A |
| 520/85R38 | 20.8R38 | 155 A8 | 516*1,849 | 20.8-38 | TR218A |

## トラクター用バイアスタイヤ



### EARTH-PRO / EARTH-PRO45

| サイズ      |     | 表記・速度  | 幅×外径         | チューブサイズ |        |
|----------|-----|--------|--------------|---------|--------|
| *8.3-20  | 6PR |        | Mitas で設定あり  | 7.50-20 | TR15   |
| 9.5-22   | 6PR | 101 A8 | 241*996      | 9.5-22  | TR218A |
| 8.3-24   | 8PR | 105 A8 | 211*998      | 8.3-24  | TR218A |
| 9.5-24   | 8PR | 112 A8 | 240*1,058    | 9.5-24  | TR218A |
| 11.2-24  | 8PR | 116 A8 | 284*1,105    | 11.2-24 | TR218A |
| 12.4-24  | 8PR | 121 A8 | 323*1,168    | 12.4-24 | TR218A |
| 13.6-24  | 8PR | 123 A8 | 345*1,210    | 13.6-24 | TR218A |
| 14.9-24  | 8PR | 128 A8 | 383*1,281    | 14.9-24 | TR218A |
| 11.2-28  | 8PR | 118 A8 | 289*1,225    | 11.2-28 | TR218A |
| 12.4-28  | 8PR | 123 A8 | 317*1,268    | 12.4-28 | TR218A |
| 13.6-28  | 8PR | 125 A8 | 345*1,310    | 13.6-28 | TR218A |
| 14.9-28  | 8PR | 130 A8 | 384*1,380    | 14.9-28 | TR218A |
| 16.9-30  | 8PR | 137 A8 | 435*1,502    | 16.9-30 | TR218A |
| 18.4-30  | 8PR | 139 A8 | 467*1,550    | 18.4-30 | TR218A |
| *12.4-32 | 8PR |        | Cultor で設定あり | 12.4-32 | TR218A |
| 16.9-34  | 8PR | 139 A8 | 433*1,585    | 16.9-34 | TR218A |
| 18.4-34  | 8PR | 142 A8 | 473*1,658    | 18.4-34 | TR218A |
| 12.4-36  | 8PR | 126 A8 | 315*1,464    | 12.4-36 | TR218A |
| 13.6-36  | 8PR | 131 A8 | 345*1,514    | 13.6-36 | TR218A |
| 12.4-38  | 6PR | 122 A8 | 315*1,516    | 12.4-38 | TR218A |
| 13.6-38  | 8PR | 127 A8 | 347*1,565    | 13.6-38 | TR218A |
| 15.5-38  | 8PR | 133 A8 | 399*1,568    | 15.5-38 | TR218A |
| 16.9-38  | 8PR | 141 A8 | 435*1,686    | 16.9-38 | TR218A |
| 18.4-38  | 8PR | 143 A8 | 463*1,760    | 16.9-38 | TR218A |

## Agriculture Tyres

ギャラクシー農業機械用タイヤ  
トラクター用バイアスタイヤ



### AGRI TRAC II R-1

| サイズ  |     | 表記・速度 | 幅×外径    | チューブサイズ    |      |
|------|-----|-------|---------|------------|------|
| 7-14 | 6PR | 80 A6 | 178*701 | 155/165-14 | TR13 |
| 7-16 | 6PR | 84 A6 | 183*743 | 6.00-16    | TR13 |
| 8-16 | 6PR | 91 A6 | 211*790 | 7.50-16    | TR13 |



### FRONT FARM F-2

| サイズ      |     | 表記・速度  | 幅×外径        | チューブサイズ |      |
|----------|-----|--------|-------------|---------|------|
| 6.00-16  | 6PR | 88 A6  | 165*735     | 6.00-16 | TR15 |
| 6.50-16  | 6PR | 91 A6  | 175*760     | 6.00-16 | TR15 |
| 7.50-16  | 8PR | 103 A6 | 205*805     | 7.50-16 | TR15 |
| 7.50-18  | 8PR | 107 A6 | 205*867     | 7.50-18 | TR15 |
| 6.00-19  | 8PR | 93 A6  | 165*814     | 6.00-19 | TR15 |
| *7.50-20 | 6PR | 103 A6 | Mitas で設定あり | 7.50-20 | TR15 |

| タイヤサイズ    |         | 標準空気圧 (bar) | 幅×外径 (mm) | チューブ    |        |
|-----------|---------|-------------|-----------|---------|--------|
| EARTH-PRO |         |             |           |         |        |
| 250/85R24 | 9.5R24  | 1.6         | 246*1,037 | 9.5-24  | TR218A |
| 280/85R24 | 11.2R24 | 1.6         | 282*1,086 | 11.2-24 | TR218A |
| 320/85R24 | 12.4R24 | 1.6         | 336*1,148 | 12.4-24 | TR218A |
| 340/85R24 | 13.6R24 | 1.6         | 356*1,181 | 13.6-24 | TR218A |
| 380/85R24 | 14.9R24 | 1.6         | 391*1,245 | 14.9-24 | TR218A |
| 420/85R24 | 16.9R24 | 1.6         | 418*1,315 | 16.9-24 | TR218A |
| 280/85R28 | 11.2R28 | 1.6         | 280*1,190 | 11.2-28 | TR218A |
| 320/85R28 | 12.4R28 | 1.6         | 325*1,246 | 12.4-28 | TR218A |
| 340/85R28 | 13.6R28 | 1.6         | 343*1,289 | 13.6-28 | TR218A |
| 380/85R28 | 14.9R28 | 1.6         | 380*1,357 | 14.9-28 | TR218A |
| 420/85R28 | 16.9R28 | 1.6         | 418*1,420 | 16.9-28 | TR218A |
| 420/85R30 | 16.9R30 | 1.6         | 438*1,468 | 16.9-30 | TR218A |
| 460/85R30 | 18.4R30 | 1.6         | 478*1,524 | 18.4-30 | TR218A |
| 320/85R32 | 12.4R32 | 1.6         | 325*1,357 | 12.4-32 | TR218A |
| 420/85R34 | 16.9R34 | 1.6         | 418*1,578 | 16.9-34 | TR218A |
| 460/85R34 | 18.4R34 | 1.6         | 479*1,637 | 18.4-34 | TR218A |
| 320/85R36 | 12.4R36 | 1.6         | 325*1,458 | 12.4-36 | TR218A |
| 340/85R36 | 13.6R36 | 1.6         | 345*1,495 | 13.6-36 | TR218A |
| 320/85R38 | 12.4R38 | 1.6         | 325*1,509 | 12.4-38 | TR218A |
| 340/85R38 | 13.6R38 | 1.6         | 345*1,543 | 13.6-38 | TR218A |
| 420/85R38 | 16.9R38 | 1.6         | 418*1,679 | 16.9-38 | TR218A |
| 460/85R38 | 18.4R38 | 1.6         | 455*1,747 | 18.4-38 | TR218A |
| 520/85R38 | 20.8R38 | 1.6         | 516*1,849 | 20.8-38 | TR218A |

| タイヤサイズ                   |     | 標準空気圧 (bar)  |           | 幅×外径 (mm)  | チューブ   |
|--------------------------|-----|--------------|-----------|------------|--------|
| EARTH-PRO45/AGMASTER R-1 |     |              |           |            |        |
| 8.3-20                   | 6PR | Mitas で設定あり  |           | 7.50-20    | TR15   |
| 9.5-22                   | 6PR | 2.2          | 241*996   | 9.5-22     | TR218A |
| 8.3-24                   | 8PR | 3.1          | 211*998   | 8.3-24     | TR218A |
| 9.5-24                   | 8PR | 2.8          | 240*1058  | 9.5-24     | TR218A |
| 11.2-24                  | 8PR | 2.4          | 284*1,105 | 11.2-24    | TR218A |
| 12.4-24                  | 8PR | 2.2          | 323*1,168 | 12.4-24    | TR218A |
| 13.6-24                  | 8PR | 2.0          | 345*1,210 | 13.6-24    | TR218A |
| 14.9-24                  | 8PR | 1.8          | 383*1,281 | 14.9-24    | TR218A |
| 11.2-28                  | 8PR | 2.4          | 289*1,225 | 11.2-28    | TR218A |
| 12.4-28                  | 8PR | 2.3          | 317*1,268 | 12.4-28    | TR218A |
| 13.6-28                  | 8PR | 2.0          | 345*1,310 | 13.6-28    | TR218A |
| 14.9-28                  | 8PR | 1.8          | 384*1,380 | 14.9-28    | TR218A |
| 16.9-30                  | 8PR | 1.7          | 435*1,502 | 16.9-30    | TR218A |
| 18.4-30                  | 8PR | 1.4          | 467*1,550 | 18.4-30    | TR218A |
| 12.4-32                  | 8PR | Cultor で設定あり |           | 12.4-32    | TR218A |
| 16.9-34                  | 8PR | 1.7          | 433*1,585 | 16.9-34    | TR218A |
| 18.4-34                  | 8PR | 1.4          | 473*1,658 | 18.4-34    | TR218A |
| 12.4-36                  | 8PR | 2.4          | 315*1,464 | 12.4-36    | TR218A |
| 13.6-36                  | 8PR | 1.6          | 345*1,514 | 13.6-36    | TR218A |
| 12.4-38                  | 6PR | 1.7          | 315*1,516 | 12.4-38    | TR218A |
| 13.6-38                  | 8PR | 2.0          | 347*1,565 | 13.6-38    | TR218A |
| 15.5-38                  | 8PR | 1.8          | 399*1,568 | 15.5-38    | TR218A |
| 16.9-38                  | 8PR | 1.7          | 435*1,686 | 16.9-38    | TR218A |
| 18.4-38                  | 8PR | 1.4          | 463*1,760 | 16.9-38    | TR218A |
| FRONT FARM F-2           |     |              |           |            |        |
| 6.00-16                  | 6PR | 3.3          | 165*735   | 6.00-16    | TR15   |
| 6.50-16                  | 6PR | 3.1          | 175*760   | 6.00-16    | TR15   |
| 7.50-16                  | 8PR | 3.7          | 205*805   | 7.50-16    | TR15   |
| 7.50-18                  | 8PR | 3.7          | 205*867   | 7.50-18    | TR15   |
| 6.00-19                  | 8PR | 3.7          | 165*814   | 6.00-19    | TR15   |
| 7.50-20                  | 8PR | Mitas で設定あり  |           | 7.50-20    | TR15   |
| AGRI TRAC II R-1         |     |              |           |            |        |
| 7-14                     | 6PR | 2.55         | 178*701   | 155/165-14 | TR13   |
| 7-16                     | 6PR | 2.5          | 183*743   | 6.00-16    | TR13   |
| 8-16                     | 6PR | 1.9          | 211*790   | 7.50-16    | TR13   |

| タイヤサイズ                          |       | 標準空気圧 (bar) | 幅×外径 (mm) | チューブ          |        |
|---------------------------------|-------|-------------|-----------|---------------|--------|
| IMPMASER200/RIB IMPLMENT        |       |             |           |               |        |
| 9.5L-15SL                       | 8PR   | 3.0         | 249*768   | 9.5L-14/15    | TR15   |
| 11L-15SL                        | 8PR   | 2.5         | 267*777   | 11L-15        | TR15   |
| 16.5L-16.1SL                    | 10PR  | 2.5         | 419*1,024 | 16.5L-16.1    | TR15   |
| 19L-16.1SL                      | 12PR  | 2.5         | 482*1,060 | 19L-16.1      | TR15   |
| 21.5L-16.1SL                    | 14PR  | 2.5         | 545*1,130 | 19L-16.1      | TR15   |
| IMPMASER350                     |       |             |           |               |        |
| 12.5L-15FI                      | 12PR  | 6.2         | 318*823   |               |        |
| DIAMOND TREAD R-3               |       |             |           |               |        |
| 23.1-26                         | 12PR  | 1.7         | 587*1,580 | 23.1-26       | TR218A |
| 28L-26                          | 16PR  | 2.2         | 714*1,590 | 28.1-26       | TR218A |
| FLOTATION I-3                   |       |             |           |               |        |
| 550/45-22.5                     | 16PR  | 2.8         | 550*1,070 | 500/45-22.5   | TR218A |
| STUBBLE PROOF R-3               |       |             |           |               |        |
| 31 × 13.50-15                   | 8PR   | 3.1         | 346*775   | 31 × 13.50-15 | TR218A |
| SUPER SOIL SOFTEE HF-2          |       |             |           |               |        |
| 750/60R26                       | 175A8 | 4.0         | 750*1,590 | 28.1-26       | TR218A |
| SUPER HIGH LIFT R-1             |       |             |           |               |        |
| 12.5/80-18                      | 14PR  | 4.25        | 307*978   | 12.5/80-18    | TR15   |
| EZ RIDER R-4, CONSTELLATION R-4 |       |             |           |               |        |
| 16.9-24                         | 12PR  | 2.6         | 429*1,295 | 16.9-24       | TR218A |
| 18.4-24                         | 12PR  | 2.5         | 467*1,375 | 18.4-24       | TR218A |
| BEEFY BABY R-4                  |       |             |           |               |        |
| 10-16.5                         | 8PR   | 4.1         | 269*792   | 10-16.5       | TR15   |
| 12-16.5                         | 10PR  | 4.5         | 314*835   | 12-16.5       | TR15   |